



Nelson & Nelson Mfg.
5210 Stadium Blvd., Suite C
Jonesboro AR 72404
870-268-6393 : Cell 219-1019

Installation Instructions 6-24-24
Model SF3RT-24CHLDR
2024+ F3/RT Cup Holder Kit

Steps needed to install your Cup Holder Kit!



- 1.- Remove the two 6mm factory Allen screws on the backside of the control module using a 3mm Allen wrench of the side you are mounting you cup holder. Left & Right sides determined by rider sitting on your Spyder.

LEFT SIDE INSTALL-Then take the preassembled cup holder as shown for a Left-side mounting using the smaller black spacer on the bottom and the larger black spacer on top. Take the new smaller Allen Head Socket bolt and install it in the lower hole. Take the longer Allen Head socket bolts and install it on the top hole. Tighten down evenly.

RIGHT SIDE INSTALL- Then take the preassembled cup holder as shown for a Right-side mounting using the black spacer on the bottom & top. Take the new Allen Head Socket bolts and install them in the lower & upper holes. Tighten down evenly.

Your New 2024+ F3 / RT Cup Holders are now installed!

We thank you for purchasing one of our Spyder Extras RT Products. We know today the needs for accessories that provide a higher level of comfort while riding and we have solved that demand with a stylish Products that complement the design of your F3 or RT !

spyderextras.com